





BUTTERFLY MX  
8" SURFACE MOUNT

51.47

46.88



DETAIL B



NOTES:

1. MATERIAL OF CONSTRUCTION IS MILD STEEL.
2. 2-4 MILS BLACK TEX POWDER COAT.

UNLESS OTHERWISE SPECIFIED:


DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL  $\pm 1/32$   
ANGULAR:  $\pm 2^\circ$   
TWO PLACE DECIMAL  $\pm 0.010$   
THREE PLACE DECIMAL  $\pm 0.005$

INTERPRET GEOMETRIC  
TOLERANCING PER:  
ASME Y14.5 -2009

NAME	DATE
DRAWN	
CHECKED	

TITLE:  
**INSTALLATION**

SIZE	PART NO.	REV
<b>A</b>	22PE1-BUT-02-CRS	<b>B</b>
WEIGHT: 16.27	NO SCALE	SHEET 1 OF 5



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	22PE1-BUT-002-CRS	2X2 SQ STEEL TUBE	1
2	8IN FACE PLATE	MOUNTING PLATE	1
3	PLTCOV-5-2	5" STANDARD COVER PLATE	1
4	PLTBAS-5-2	5" STANDARD BASE PLATE	1
5	--	316 STAINLESS STEEL ULTRA-LOW-PROFILE SOCKET HEAD SCREW 8-32 X 5/16"	4
6	--	18-8 STAINLESS STEEL CAP NUT 8-32	4

NOTES:

1. BUTT WELDED SECTIONS ARE NOT ALLOWED, EACH SECTION OF TUBE MUST BE FROM CONTINUOUS STOCK.
2. ALL WELDS ARE TO BE CONTINUOUS FILLET WELDS UNLESS NOTED OTHERWISE.
3. SEE STANDARD PREPARATION AND COATING INSTRUCTIONS FOR COATING PROCEDURE AND COLOR.
4. FASTENERS ARE TO BE BAGGED AND SHIPPED WITH PEDESTAL.
5. SEE STANDARD PACKAGING INSTRUCTIONS FOR PACKAGING PROCEDURE.

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES  
 TOLERANCES:  
 FRACTIONAL  $\pm 1/32$   
 ANGULAR:  $\pm 2^\circ$   
 TWO PLACE DECIMAL  $\pm 0.010$   
 THREE PLACE DECIMAL  $\pm 0.005$

INTERPRET GEOMETRIC  
 TOLERANCING PER:  
 ASME Y14.5 -2009

NAME	DATE
DRAWN	
CHECKED	

TITLE:  
**ASSEMBLY**

SIZE <b>A</b>	PART NO. 22PE1-BUT-02-CRS	REV <b>B</b>
WEIGHT: 16.27	NO SCALE	SHEET 2 OF 5