

Image: Notes Notes 2 PLTCAP-84-84-30 CAP 3 PLTAC-510 ACCESS PANEL 4 PLTAS-584-84 BASE PLATE 5 - 8-32 x 1/2' SS BUTTON HEAD SCREW 4 PLTAS-584-84 BASE PLATE 5 - 8-32 x 1/2' SS BUTTON HEAD SCREW 4		ITEM N	10	P		JMBER		DESCRIPTION		TY.
2 PLTCAP-84-84-30 CAP 1 3 PLTACC-510 ACCESS PANEL 1 4 PLTBAS-84-84 BASE PLATE 1 5 - B-32 X 1/2" SS BUTTON HEAD SCREW 4 0 - B-32 X 1/2" SS BUTTON HEAD SCREW 4 0 - B-32 X 1/2" SS BUTTON HEAD SCREW 4 1 Screen and the screen		1					TOWFR W			
3 PLTACC-510 ACCESS PANEL 1 4 PLTBAS-84-84 BASE PLATE 1 5 - 8-32 X 1/2' SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2' SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2' SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2' SS BUTTON HEAD SCREW 4 1 Science Science 8-32 X 1/2' SS BUTTON HEAD SCREW 4 1 Science Science 8-32 X 1/2' SS BUTTON HEAD SCREW 4 1 Science Science Science 4 4 1 Science Science Science 4 4		2								1
1 4 PLIBAS-84-84 BASE PLATE 1 1 5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 3 - - - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 3 - - - - - - - 3 -								PANEL		1
5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 5 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 0 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 0 - 8-32 X 1/2" SS BUTTON HEAD SCREW 4 1 SEE STANDARD PREPARATION AND COATING INSTRUCTIONS FOR COATING PROCEDURE AND COLOR. 1. SEE STANDARD PREPARATION AND COATING INSTRUCTIONS FOR COATING PROCEDURE AND COLOR. 1 SEE STANDARD PREPARATION AND COATING INSTRUCTIONS FOR COATING PROCEDURE AND COLOR. 0. 1 SEE STANDARD PREPARATION AND COATING INSTRUCTIONS FOR COATING PROCEDURE AND COLOR. 1 SEE STANDARD PREPARATION AND COATING INSTRUCTIONS FOR COATING PROCEDURE AND COLOR. 1 SEE STANDARD PACKAGING INSTRUCTIONS FOR PACKAGING PROCEDURE. 1 WWW.GoosneckStands.com Mediate 32 minutes and the structure of coating prevention of the structure of coati	(2)		PLTI	BAS-84	-84		BASE PLA	TE		1
MOTES: 5 1 SEE STANDARD PREPARATION AND COATING INSTRUCTIONS FOR COATING PROCEDURE AND COLOR. 2 SEE STANDARD PACKAGING INSTRUCTIONS FOR PACKAGING PROCEDURE. www.GoosneckStands.com (888) 378 - 1045 Imensions are in inches tolerances: Adless@GooseneckStands.com Imensions are in inches tolerances: Anciulae: 12' Modulae: 12' M							8-32 X 1/2	" SS BUTTON HEAD SCRE	W	4
(888) 378 - 1045 Sales@GooseneckStands.com INTERPRET GEOMETRIC IN	5			NAME	1. 2.	SEE STANDAR FOR COATING SEE STANDAR PROCEDURE.	G PROCED	URE AND COLOR.		
(888) 378 - 1045 Sales@GooseneckStands.com INTERPRET GEOMETRIC IN	www.GoosneckStands.com		DRAWN				V			
(888) 378 - 1045 Two PLACE DECIMAL ±0.010 THREE PLACE DECIMAL ±0.005 Sales@GooseneckStands.com INTERPRET GEOMETRIC TO FERANCING PER: TWO PLACE DECIMAL ±0.010 THREE PLACE DECIMAL ±0.005 INTERPRET GEOMETRIC TO FERANCING PER: TWO PLACE DECIMAL ±0.010 THREE PLACE DECIMAL ±0.005 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PEDESTALPRO LIC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PEDESTALPRO LIC. TO FERANCING PER: THREE PLACE DECIMAL ±0.010 THREE PLACE DECIMAL ±0.005 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PEDESTALPRO LIC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PEDESTALPRO LIC.		FRACTIONAL±1/32 ANGULAR: ±2° TWO PLACE DECIMAL ±0.010	CHECKED	CKED		HUSEINIDEI	. T			
Sales@GooseneckStands.com Interpret geometric toterancing per: Drawing is the sole property of pedestalero Lic. any reproduction in part or as a whole without the written persussion of pedestalero Lic. 2:39:58 PM A 84TOW-COMM-01-304 A	(888) 378 - 1045							SIZE PART NO.		REV
TOLERANCING PER: WRITEN PERMISSION OF PEDESTAL PRO LLC	Sales@GooseneckStands.com		DRAWING IS THE PEDESTALPRO LL	SOLE PROPER C. ANY REPRO	TY OF DUCTION	2:39:58	PM	A 84TOW-COMM-01	-304	Α
		TOLERANCING PER:	WRITTEN PERMISSION OF PEDESTALPRO LLC			WEIGHT: 55.832		NO SCALE	SHEET 2 OF	- 7